


# X-keys® USB Encoder Board Specifications

for XK-0988-UNM128-R



- 128 Switch Points
- $\pi$ 3 firmware, which feature HID keyboard, mouse and joystick hardware emulation
- Includes programming software for Windows and Mac
- Free software development kits for developers

The X-keys®  $\pi$ 3 Matrix Encoder Board uses the same electronic design as our X-keys Programmable Keyboards and Foot Pedals. X-keys devices work in cooperation with a standard keyboard. Each of the 128 switch points can be programmed with multiple keystrokes, combinations, mouse functions, game controller (joystick) actions and more. Programming is easily accomplished via our included X-keys MacroWorks 3 software for Windows (XP, Vista, or 7) and programmers can use one of our SDKs for Windows or Linux to read data directly from the X-keys.

## Unit Specifications

<b>Connector Type</b>	USB "A" plug
<b>Input Connector</b>	0.1" double row, 30 pin female header receptacle (not included)
<b>Number of Inputs</b>	128 possible matrix points (switches)
<b>Dimensions</b>	2" x 1.3" x 0.58", (50.8mm x 33mm x 15mm)
<b>Weight</b>	2.56 oz. (73 grams)
<b>Cord Length</b>	8' (2.44 m)
<b>Power Consumption</b>	Low power USB device, less than 15 ma @ 5 vdc
<b>Power Source</b>	USB port power, nominal voltage = 5 vdc
<b>Certification</b>	FCC Class B, CE
<b>Software Mode Features</b>	
<b>Operating System</b>	Windows XP, Vista, 7
<b>Included Software</b>	MacroWorks 3 (Windows), ControllerMate (Mac OS X)
<b>Available Software</b>	Windows and Linux SDKs (free download)
<b>Layers</b>	MW3 supports multiple layers including application specific programming.
<b>Hardware Mode Features</b>	
<b>Hardware System</b>	Any architecture supporting USB, including Sun, SGI, and HP workstations
<b>Operating System</b>	Programming requires MacroWorks 3 for Windows XP, Vista or 7. Operates on any OS supporting USB including Unix, Sun and Mac OS-X
<b>Memory Capacity</b>	Each matrix point is allocated 3 characters and a pool of 560 additional keystrokes is available to any switches requiring additional characters
<b>Memory Type</b>	EEPROM, non volatile memory (X-keys retains memory for over 200 years)
<b>Layers</b>	2 layers – user selectable toggle and/or shift function

Specifications subject to change without notice

P.I. Engineering, Inc.  
101 Innovation Parkway | Williamston, Michigan 48895-1663  
Phone: (517) 655-5523 | Fax: (517) 655-4926  
E-mail: tech@xkeys.com | Web: www.xkeys.com

