

X-keys® Four, Six, and Eight Button Pendant Switches Specifications

for XK-A-1433-PDT4-R, XK-A-1434-PDT6-R, and XK-A-1435-PDT8-R



- Perfect for use with the X-keys HD15 USB Wire Interface
- Rugged design for Assistive Technology or industrial application
- Uses standard 15 pin extension cable of any length
- Designed for signal level control (not for high voltage or high current)

The X-keys Pendant Switches are rugged industrial buttons to trigger any action on a computer. Perfect for CNC router, machine control on any computer driven process, or any application where a remote pendant control makes an operator safer and more efficient.

Specifications

Dimensions	2"(50mm) high x 2.7"(68mm) wide
Length	4 Button: 7.9"(20cm) 6 Button: 10.2"(26cm) 8 Button: 12.6"(32cm)
Weight	4 Button: 0.6lb (272g) 6 Button: 0.75lb (340g) 8 Button: 0.95lb (431g)
Actuation Force	Approx. 27 oz (770 g)
Connector Type	HD15 female
Mounting	0.15" (3mm) dia hole in molded tang
Case Material	Commercial duty ABS plastic
Voltage	Less than 32 volts
Current	Less than 1 Amp
Conductors	Rated for Severe Duty
RoHS	Compliant

Specifications subject to change without notice