

X-keys® XK-68 Jog & Shuttle Specifications

for XK-0990-UBG68-R



- 68 Programmable keys with Jog Wheel and Shuttle Ring
- Includes software for Windows and Mac
- Free Software Development Kit for programmers
- Two color addressable backlighting (red and blue)

The X-keys XK-68 Jog & Shuttle controller features 68 keys with independent backlighting plus a jog wheel and shuttle ring. The co-injected case with soft sides for hand-held or desktop applications suits portrait or landscape orientation. A pair of snap in feet give the X-keys a slight angle on the desktop.

MacroWorks 3 software for Windows and ControllerMate software for Mac OS-X combine ease of programming with a wide and flexible range of options. P.I. Engineering's Pi3 firmware supports direct communication for the software developer and our new reflector feature sends messages to even the most reluctant software.

Specifications

Operating System	Use: Any OS via USB HID Programming: Windows XP through 10, Mac OS X 10.4 through 10.10
Free Programming Software	Windows: MacroWorks 3.1 Mac: ControllerMate for X-keys
Free Software Development Kits	Windows (C++, C#, VB.NET), Linux (C++), Android (Java), raw HID (any language/OS)
Emulation Modes	HID keyboard, HID mouse, HID game controller
Jog Control	10 detent, independent clockwise and counter clockwise commands
Shuttle Control	Independent macros for left and right with increasing repeat rate moving away from center (spring return to rest). Other commands available through scripting.
Switch Type	Full-travel rubber dome, carbon on gold contacts, guaranteed for over 1 million operations
Number of Keys	68 single keys, 1 programming button
Actuation Force	Approx. 2.5 oz (72g) break-over, approx. 1.5 oz (42g) hold
Keycaps	0.625" (16mm) sq.; relegendable with Cherry MX compatible stem
Key Spacing	0.75" O.C.
Optional Keys	2x1, 1x2, 2x2, and 1x1 blocker
Backlighting	1 blue and 1 red addressable LED under each key
Connector	Wired USB 2.0 standard "A" plug
Cord Length	56" (1.42 m)
Dimensions	8.25" x 7.25" x 0.94" (210mm x 184mm x 24xm)
Weight	26 oz. (737 g)
USB type	USB 1.1 (compatible through 3.0)
Power Source	USB port, nominal voltage = 5 vdc
Power Consumption	No backlight: 20 mA , Blue backlight full: 30 mA, Red backlight full: 39 mA, All backlights: 50 mA
Temperature Range	-20 to 60 C
Memory Capacity	Approximately 21,000 keystrokes or commands in onboard memory
Memory Type	EEPROM, non volatile memory (X-keys retains memory for over 200 years)
Environmental Rating	IP 40, typical indoor office environment
Certifications	FCC class B, CE, RoHS, WEEE compliant

Specifications subject to change without notice

P.I. Engineering, Inc.
101 Innovation Parkway | Williamston, Michigan 48895-1663
Phone: (517) 655-5523 | Fax: (517) 655-4926
E-mail: tech@xkeys.com | Web: www.xkeys.com

